

## LIFTING BEAMS

Economy H-Beam



### ECONOMY H-BEAM

1,000 LB WLL		TOP BEAM: L MIN / L MAX		
		PART NUMBER		
		12"-48"	36"-72"	60"-96"
LOWER BEAMS: W MIN / W MAX	12"-48"	<b>17560</b>	<b>17563</b>	<b>17566</b>
	HR	15.1	15.1	16.1
	WEIGHT	135	150	185
	36"-72"	<b>17561</b>	<b>17564</b>	<b>17567</b>
	HR	15.1	15.1	16.1
	WEIGHT	165	180	215
	60"-96"	<b>17562</b>	<b>17565</b>	<b>17568</b>
	HR	15.1	15.1	16.1
	WEIGHT	195	210	245

\* Call for specifications on larger sizes and capacities

2,000 LB WLL		TOP BEAM: L MIN / L MAX		
		PART NUMBER		
		12"-48"	36"-72"	60"-96"
LOWER BEAMS: W MIN / W MAX	12"-48"	<b>17569</b>	<b>17572</b>	<b>17575</b>
	HR	16.1	17.1	17.1
	WEIGHT	150	180	250
	36"-72"	<b>17570</b>	<b>17573</b>	<b>17576</b>
	HR	17.1	17.1	18.1
	WEIGHT	170	200	340
	60"-96"	<b>17571</b>	<b>17574</b>	<b>17577</b>
	HR	17.1	17.1	18.1
	WEIGHT	240	270	340

\* Call for specifications on larger sizes and capacities

4,000 LB WLL		TOP BEAM: L MIN / L MAX			
		PART NUMBER			
		12"-48"	36"-72"	60"-96"	84"-120"
LOWER BEAMS: W MIN / W MAX	12"-48"	<b>17578</b>	<b>17582</b>	<b>17586</b>	<b>17590</b>
	HR	18.1	19.1	20.1	20.1
	WEIGHT	185	245	360	415
	36"-72"	<b>17579</b>	<b>17583</b>	<b>17587</b>	<b>17591</b>
	HR	19.1	19.1	21.1	21.1
	WEIGHT	255	285	400	455
	60"-96"	<b>17580</b>	<b>17584</b>	<b>17588</b>	<b>17592</b>
	HR	19.1	19.1	20.1	20.1
	WEIGHT	365	425	540	595
	84"-120"	<b>17581</b>	<b>17585</b>	<b>17589</b>	<b>17593</b>
	HR	19.1	19.1	21.1	21.1
	WEIGHT	425	485	600	655

\* Call for specifications on larger sizes and capacities

8,000 LB WLL		TOP BEAM: L MIN / L MAX		
		PART NUMBER		
		24"-72"	48"-96"	72"-120"
LOWER BEAMS: W MIN / W MAX	12"-48"	<b>17598</b>	<b>17602</b>	<b>17606</b>
	HR	25.6	25.6	25.6
	WEIGHT	305	410	565
	36"-72"	<b>17599</b>	<b>17603</b>	<b>17607</b>
	HR	26.6	26.6	26.6
	WEIGHT	425	530	685
	60"-96"	<b>17600</b>	<b>17604</b>	<b>17608</b>
	HR	27.6	27.6	27.6
	WEIGHT	655	760	915
	84"-120"	<b>17601</b>	<b>17605</b>	<b>17609</b>
	HR	27.6	27.6	27.6
	WEIGHT	765	870	1,025

\* Call for specifications on larger sizes and capacities

- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Painted safety yellow for increased visibility.
- **ALL** Lifting Beams proof loaded and shipped with certification paperwork.
- Durable construction ideally suited to jobsite or warehouse use.
- Made in U.S.A.
- Custom designs available - call for engineering.
- **ALL** lifting equipment individually proof loaded per OSHA requirements.
- All dimensions in inches unless otherwise noted.
- Standard with Shackles

Prop 65 – See Page 102

- Quick and easy adjustment of unbalanced loads.
- Ideally suited to low headroom applications.
- Eye hooks and custom connections available - call for ordering assistance.

