


SYNTHETIC POLYESTER WEBBING SLINGS

- Manufactured to exceed all ASME B30.9 and OSHA 1910.184 regulations.
- Durable, heavy-duty tags ideally suited to jobsite or warehouse use.
- Custom tagging available - call for details.
- All dimensions in inches unless otherwise noted.

- Order length in feet in the '-X' portion of part number.

 Prop 65 – See Page 102



TYPE III

Sling is made with a flat loop on each end with loop eye opening on the same plane as the sling body. This type of sling is sometimes called a flat eye and eye, eye and eye, or double eye sling. Web width of 3” and above come standard with tapered eyes. Triple and quadruple ply sling eyes cannot be tapered.

Web Width	Part Number	WORKING LOAD LIMIT IN POUNDS		
		Vertical	Choker	Basket
SINGLE PLY				
1	EE1-901-X	1,600	1,280	3,200
2	EE1-902-X	3,200	2,560	6,400
3	EE1-903-X	4,800	3,840	9,600
4	EE1-904-X	6,400	5,120	12,800
5	EE1-905-X	8,000	6,400	16,000
6	EE1-906-X	9,600	7,680	19,200
7	EE1-908-X	12,800	10,240	25,600
8	EE1-9010-X	16,000	12,800	32,000
9	EE1-9012-X	19,200	15,360	38,400
DOUBLE PLY				
1	EE2-901-X	3,200	2,560	6,400
2	EE2-902-X	6,400	5,120	12,800
3	EE2-903-X	8,880	7,104	17,760
4	EE2-904-X	11,520	9,216	23,640
6	EE2-906-X	16,320	13,056	32,640