


**CONCRETE PIPE LIFTING**

- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Wire rope lifting sling available - call for quote.
- Wire rope ferrules available separately - order by part number and wire rope diameter.
- Durable construction ideally suited to jobsite use.
- Made in U.S.A.
- Efficient method for handling of water and sewer concrete pipes.

 Prop 65 – See Page 102

Capacity in Pounds*	Teacup Part Number	Wire Rope Diameter	X	Y	Z	Color		Wire Rope Ferrule Part Number
4,400	<b>11575</b>	1/2"	5.00	6.00	3.50	Orange		<b>12370</b>
6,800	<b>11576</b>	5/8"	5.00	6.00	3.50	Gray		<b>12371</b>
9,800	<b>11577</b>	3/4"	5.00	6.00	3.50	Blue		<b>12372</b>
13,200	<b>11578</b>	7/8"	5.00	6.00	3.50	Black		<b>12373</b>
17,000	<b>11579</b>	1"	5.00	6.00	4.25	Red		<b>12374</b>
20,000	<b>11580</b>	1-1/8"	5.00	6.00	4.25	Green		<b>12375</b>
26,000	<b>11581</b>	1-1/4"	6.00	7.50	5.00	Yellow		<b>12376</b>
30,000	<b>11582</b>	1-3/8"	6.00	7.50	5.00	White		<b>12380</b>
36,000	<b>11583</b>	1-1/2"	6.00	7.50	5.50	Orange		<b>12381</b>
50,000	<b>11783</b>	1-3/4"	6.00	7.50	5.50	Brown		<b>12421</b>

\* Call for specifications on larger sizes and capacities

