


CONCRETE PIPE LIFTING

- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Wire rope lifting sling available - call for quote.
- Wire rope ferrules available separately - order by part number and wire rope diameter.
- Durable construction ideally suited to jobsite use.
- Made in U.S.A.
- Efficient method for handling of water and sewer concrete pipes.

 Prop 65 – See Page 104

Capacity in Pounds*	Teacup Part Number	Wire Rope Diameter	X	Y	Z	Color		Wire Rope Ferrule Part Number
4,400	11575	1/2"	5.00	6.00	3.50	Orange		12370
6,800	11576	5/8"	5.00	6.00	3.50	Gray		12371
9,800	11577	3/4"	5.00	6.00	3.50	Blue		12372
13,200	11578	7/8"	5.00	6.00	3.50	Black		12373
17,000	11579	1"	5.00	6.00	4.25	Red		12374
20,000	11580	1-1/8"	5.00	6.00	4.25	Green		12375
26,000	11581	1-1/4"	6.00	7.50	5.00	Yellow		12376
30,000	11582	1-3/8"	6.00	7.50	5.00	White		12380
36,000	11583	1-1/2"	6.00	7.50	5.50	Orange		12381
50,000	11783	1-3/4"	6.00	7.50	5.50	Brown		12421

\* Call for specifications on larger sizes and capacities

