

**CUSTOM SPREADER BEAM HD END CAP KITS**

- Manufactured to exceed all ASME B30.20 and OSHA regulations. when assembled to specifications using A53 Grade B Schedule 80 pipe.
  - Painted safety yellow for increased visibility.
  - **ALL** End Caps shipped with proof load certification paperwork.
  - Durable construction ideally suited to jobsite or warehouse use.
  - Made in U.S.A.
- Top rigging available - call for details.
  - **ALL** lifting equipment individually proof loaded per OSHA requirements.
  - Minimum horizontal top rigging angle of 45° - M&W recommends a minimum angle of 60°.
- Prop 65 – See Page 112

|             |              | OUTSIDE SPREAD IN FEET / WLL IN POUNDS ***45 OR 60 DEGREE TOP RIGGING |         |         |         |         |         |         |         |         |
|-------------|--------------|---|---------|---------|---------|---------|---------|---------|---------|---------|
| Part Number | Weight       | 6'  | 8'      | 10'     | 15'     | 20'     | 25'     | 30'     | 35'     | 40'     |
| 22525       | 425 LBS each | 160,000   | 160,000 | 160,000 | 160,000 | 160,000 | 160,000 | 160,000 | 150,000 | 100,000 |

| Optional Sleeve | Weight  |
|-----------------|---------|
| 22524           | 185 LBS |

