

- Manufactured to exceed all ASME B30.9 and OSHA 1910.184 regulations.
  - Durable, heavy-duty tags ideally suited to jobsite or warehouse use.
  - Custom tagging available - call for details.
  - All dimensions in inches unless otherwise noted.
- **Order length in feet in the '-X' portion of part number.**

 Prop 65 – See Page 112



**INSPECTION AND REPAIR**

Slings should be examined throughout their length for abrasions, cuts, heat damage, fitting distortion or damage, and tag legibility. Abrasion, heat damage, or cuts to the cover may indicate a loss of strength to the load cores. If any doubts are held by the inspector, sling should be removed from service and sent to M&W for evaluation and possible repair. Slings removed from service shall be destroyed and rendered completely unfit for future use. Inspector and sling user shall follow all applicable OSHA 1910.184 and ASME B30.9-6 regulations regarding sling use and inspection.

Part Number	Color	RATED CAPACITIES IN POUNDS			Approx. Width	Approx. Weight Pounds/Foot	Shortest Possible Leg Length
		Vertical	Choker	Basket			
<b>PNR3-X</b>	Purple	3,000	2,400	6,000	2"	.30	3'
<b>PNR4-X</b>	Black	4,500	3,600	9,000	2"	.45	3'
<b>PNR6-X</b>	Green	6,000	4,800	12,000	2"	.48	3'
<b>PNR9-X</b>	Yellow	9,000	7,200	18,000	2"	.70	3'
<b>PNR12-X</b>	Grey	12,000	9,600	24,000	3"	.90	3'
<b>PNR14-X</b>	Red	14,000	11,200	28,000	3"	.95	3'
<b>PNR17-X</b>	Brown	17,000	13,600	34,000	3"	1.20	3'
<b>PNR22-X</b>	Blue	22,000	17,600	44,000	3"	1.40	3'
<b>PNR26-X</b>	Orange	26,000	20,800	52,000	4"	1.70	3'
<b>PNR32-X</b>	Orange	32,000	25,600	64,000	4"	1.90	4'
<b>PNR40-X</b>	Orange	40,000	32,000	80,000	5"	2.40	4'
<b>PNR50-X</b>	Orange	50,000	40,000	100,000	5"	2.70	4'
<b>PNR60-X</b>	Orange	60,000	48,000	120,000	5"	3.00	4'
<b>PNR70-X</b>	Black	70,000	56,000	140,000	6"	3.50	5'
<b>PNR80-X</b>	Black	80,000	64,000	160,000	6"	4.00	5'
<b>PNR90-X</b>	Black	90,000	72,000	180,000	6"	4.50	5'
<b>PNR100-X</b>	Black	100,000	80,000	200,000	6"	5.00	5'