


- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Painted safety yellow for increased visibility.
- **ALL** Lifting Beams proof loaded and shipped with certification paperwork.
- Durable construction ideally suited to warehouse use.
- Made in U.S.A.
- Custom designs available - call for engineering.
- **ALL** lifting equipment individually proof loaded per OSHA requirements.
- Supplied with shackles.




Prop 65 – See Page 112

Working Load Limit in Pounds*	Part Number	Bale Width	Bale Height	HR	Width	Weight in Pounds	Bottom Shackle Size
500	20347	2	4	6.8	12	8	3/8"
500	20348	2	4	6.8	24	15	3/8"
500	20349	2	4	6.8	36	21	3/8"
2,000	20350	3	5	9.8	12	18	5/8"
2,000	20351	3	5	9.8	24	31	5/8"
2,000	20352	3	5	9.8	36	45	5/8"
6,000	20353	3	5	10.8	12	26	3/4"
6,000	20354	3	5	10.8	24	48	3/4"
6,000	20355	3	5	10.8	36	69	3/4"
10,000	24031	3	5	13	12	34	3/4"
10,000	24032	3	5	13	24	56	3/4"
10,000	24033	3	5	13	36	80	3/4"
20,000	20356	4	7	16.1	24	92	7/8"
20,000	20357	4	7	16.1	36	129	7/8"
40,000	24034	5	9	25	24	225	1 1/4"
40,000	24035	5	9	25	36	300	1 1/4"
80,000	24036	7	14	31	24	460	1 3/4"
80,000	24037	7	14	31	36	600	1 3/4"

* Call for specifications on larger sizes and capacities

STANDARD WITH SHACKLES



SHOWN WITH OPTIONAL HOOKS

