Basket Lifting Beam

- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Painted safety yellow for increased visibility.
- **ALL** Lifting Beams proof loaded and shipped with certification paperwork.
- Durable construction ideally suited to jobsite or warehouse use.
- Made in U.S.A.
- Custom designs available - call for engineering.
- **ALL** lifting equipment individually proof loaded per OSHA requirements.
- All dimensions in inches unless otherwise noted.

- Designed to be used with lifting slings in a basket hitch
- Two sets of lifting sling hooks are standard
- Hooks designed for 2” eye width
- Custom configurations available - call for ordering assistance



RFID TRACKING
CHIP EQUIPPED



Working Load Limit in Pounds*	Model Number Headroom (in) Weight (lbs)	Outside Spread (L) in Feet*							A (in) B (in) E (in)
		4	6	8	10	12	14	16	
1,000	**Part Number**	**17492**	**17493**	**17494**	**17495**	**17496**	**17497**	**17498**	3.0
	HR =	9.50	9.50	9.50	9.50	9.50	9.50	10.50	5.0
	LBS =	65	80	100	120	205	235	315	2.0
2,000	**Part Number**	**17499**	**17500**	**17501**	**17502**	**17503**	**17504**	**17505**	3.0
	HR =	9.50	9.50	10.50	10.50	10.50	11.50	11.50	5.0
	LBS =	65	80	175	210	245	325	370	2.0
4,000	**Part Number**	**17506**	**17507**	**17154**	**17508**	**17509**	**17510**	**17511**	3.0
	HR =	10.50	10.50	11.50	11.50	12.50	13.50	13.50	5.0
	LBS =	110	150	210	310	340	580	660	2.0
10,000	**Part Number**	**17512**	**17513**	**17514**	**17515**	**17516**	**17517**	**16574**	3.0
	HR =	16.37	16.37	16.37	17.37	17.37	17.37	17.37	5.0
	LBS =	260	340	425	510	720	965	1,090	2.0

* Call for specifications on larger sizes and capacities