

- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Painted safety yellow for increased visibility.
- **ALL** Spreader Beams shipped with proof load certification paperwork.
- Durable construction ideally suited to jobsite or warehouse use.
- Standard with swivel latch hooks. Top rigging not included - please call for pricing
- Made in U.S.A.
- Custom designs available - call for engineering.
- Minimum horizontal top rigging angle of 45°.

Prop 65 – See Page 112



**SHOWN WITH  
OPTIONAL  
TOP  
RIGGING**



FIXED LENGTH SPREADER BEAM											
Working Load Limit in Pounds*	Model Number Headroom (in) Weight (lbs)	Outside Spread (L) in Feet*									A (in) C (in) E (in)
		4	6	8	10	12	16	20	25	30	
4,000	<b>Part Number</b>	<b>13094</b>	<b>13097</b>	<b>13100</b>	<b>13103</b>	<b>13106</b>	<b>13109</b>	<b>13112</b>	<b>24473</b>	<b>24474</b>	1.00
	HR =	7.37	7.37	8.12	8.12	8.12	8.12	8.12	9.0	9.1	0.50
	LBS =	55	75	95	115	135	180	218	380	455	.089
10,000	<b>Part Number</b>	<b>13116</b>	<b>13119</b>	<b>13122</b>	<b>13125</b>	<b>13128</b>	<b>13131</b>	<b>13134</b>	<b>24475</b>	<b>24476</b>	1.31
	HR =	8.23	8.98	8.98	8.98	9.98	9.98	9.98	11.0	11.3	0.75
	LBS =	75	105	135	165	195	255	315	578	690	1.08
20,000	<b>Part Number</b>	<b>13138</b>	<b>13141</b>	<b>13144</b>	<b>13147</b>	<b>13150</b>	<b>13153</b>	<b>13156</b>	<b>24477</b>	<b>24478</b>	1.66
	HR =	9.25	11.00	11.00	11.00	11.00	12.00	12.00	13.0	13.0	1.00
	LBS =	125	165	210	255	300	385	475	895	1065	1.31

OPTIONAL TOP RIGGING										
Working Load Limit in Pounds*	Part Name	Part Number	Part Number	Part Number	Part Number	Part Number	Part Number	Part Number	Part Number	Part Number
4,000	<b>Fixed Spreader</b>	<b>13094</b>	<b>13097</b>	<b>13100</b>	<b>13103</b>	<b>13106</b>	<b>13109</b>	<b>13112</b>	<b>24473</b>	<b>24474</b>
	Chain	23354	23354	23355	23355	23356	23357	23357	24456	24456
	Wire Rope	23396	23396	23397	23397	23398	23399	23399	24462	24462
	Round Sling Bridle	23374	23374	23375	23375	23376	23377	23377	24459	24459
10,000	<b>Fixed Spreader</b>	<b>13116</b>	<b>13119</b>	<b>13122</b>	<b>13125</b>	<b>13128</b>	<b>13131</b>	<b>13134</b>	<b>24475</b>	<b>24476</b>
	Chain	23378	23378	23379	23379	23380	23381	23381	24457	24457
	Wire Rope	23400	23400	23401	23401	23402	23403	23403	24463	24463
	Round Sling Bridle	23382	23382	23383	23383	23384	23385	23385	24460	24460
20,000	<b>Fixed Spreader</b>	<b>13138</b>	<b>13141</b>	<b>13144</b>	<b>13147</b>	<b>13150</b>	<b>13153</b>	<b>13156</b>	<b>24477</b>	<b>24478</b>
	Chain	23386	23386	23387	23387	23388	23389	23389	24458	24458
	Wire Rope	23404	23404	23405	23405	23406	23407	23407	24464	24464
	Round Sling Bridle	23390	23390	23391	23391	23392	23393	23393	24461	24461