


SPREADER BEAMS

Fixed Spread Large Capacity Shackle End

SHOWN WITH
OPTIONAL TOP
RIGGING & SHACKLES



- Manufactured to exceed all ASME B30.20 and OSHA regulations.
- Painted safety yellow for increased visibility.
- ALL Spreader Beams shipped with proof load certification paperwork.
- Durable construction ideally suited to jobsite or warehouse use.
- Made in U.S.A.
- Custom designs available - call for engineering.
- ALL lifting equipment individually proof loaded per OSHA requirements.

 Prop 65 – See Page 112

FIXED LENGTH LARGE CAPACITY SHACKLE END SPREADER BEAMS												
Working Load Limit in Pounds*	Shackle Size	Model Number Headroom (in) Weight (lbs)	Outside Spread (L) in Feet*									
			4	6	8	10	12	16	20	25	30	
40,000	1-1/2" Top 1-1/2" Bottom	Part Number	20165	20166	20167	20168	20169	20170	20171	24479	24480	
		HR =	8	8	8	8	8	8	8	8	8	8
		LBS =	215	275	330	385	440	550	660	910	1066	
60,000	1-3/4" Top 1-3/4" Bottom	Part Number	20172	20173	20174	20175	20176	20177	20178	24481	24482	
		HR =	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6
		LBS =	255	320	385	450	510	635	770	1493	1770	
80,000	2" Top 2" Bottom	Part Number	20179	20180	20181	20182	20183	20184	20185	24483	24484	
		HR =	9.8	9.8	9.8	9.8	9.8	9.8	9.8	9.8	9.8	9.8
		LBS =	390	475	550	635	715	875	1,050	1496	1735	
100,000	2" Top 2" Bottom	Part Number	20186	20187	20188	20189	20190	20191	20192	24485	24486	
		HR =	9.8	9.8	9.8	9.8	9.8	9.8	9.8	9.8	9.8	9.8
		LBS =	390	475	550	635	715	875	1,050	1496	1735	
150,000	2-1/2" Top 2-1/2" Bottom	Part Number	24503	24502	24501	24500	24499	24498	24497	24487	24488	
		HR =	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
		LBS =	820	968	1116	1264	1412	1707	2008	2371	2740	

*Minimum horizontal top rigging angle is 45° on all fixed and adjustable spreaders. M&W recommends a minimum horizontal top rigging angle of 60°.

OPTIONAL RIGGING										
Working Load Limit in Pounds*	Part Name	Part Number	Part Number	Part Number	Part Number	Part Number	Part Number	Part Number	Part Number	Part Number
40,000	Fixed Spreader	20165	20166	20167	20168	20169	20170	20171	24479	24480
	Wire Rope	23421	23421	23422	23422	23423	23424	23424	24414	24414
	Round Sling Bridle	23433	23433	23434	23434	23435	23436	23436	24422	24422
60,000	Fixed Spreader	20172	20173	20174	20175	20176	20177	20178	24481	24482
	Wire Rope	23425	23425	23426	23426	23427	23428	23428	24415	24415
	Round Sling Bridle	23437	23437	23438	23438	23439	23440	23440	24423	24423
80,000	Fixed Spreader	20179	20180	20181	20182	20183	20184	20185	24483	24484
	Wire Rope	23430	23430	23430	23430	23431	23432	23432	24416	24416
	Round Sling Bridle	23441	23441	23442	23442	23443	23444	23444	24424	24424
100,000	Fixed Spreader	20186	20187	20188	20189	20190	20191	20192	24485	24486
	Wire Rope	23430	23430	23430	23430	23431	23432	23432	24416	24416
	Round Sling Bridle	23441	23441	23442	23442	23443	23444	23444	24424	24424
150,000	Fixed Spreader	24503	24502	24501	24500	24499	24498	24497	24487	24488
	Round Sling	24418	24418	24418	24417	24417	24426	24426	24425	24425